



ITEM	PART #	MATERIAL	QTY	ITEM	PART #	MATERIAL	QTY
a	4310	Insulator, Pin Type	3	bs	9376	Upset Bolt - 5/8"	1
b	4410	Pin, Pole Top	1	cm	9471	Insulator, Spool - 3"	1
c1	9371-6	Bolt, Machine - 1/2"	2	cu	2040	Brace, 84" X 24"	2
c2	9372	Bolt, Machine - 5/8"	6	ek	9094	Locknuts, 1/2"	2
c3	9373	Bolt, Machine - 3/4"	1	ek	9096	Locknuts, 5/8"	7
d1	9098	Washer, Round - 1/2"	2	ek	9097	Locknuts, 3/4"	1
d2	9091	Washer, Square - 2"X2"	10	rp1	4766	Perch Guard 36"	2
d3	9093	Washer, Curved 3"- 13/16"	1	rp5	4780	Zena Spikes	1
d4	9091-4	Washer, Square 4"- 13/16"	1	rp6	4772	Perch Guard, Pole Top	1
f	4375	Pins, Crossarm Saddle	2	rp7	4769	Perch Guard Extensions	2
g	4090	Crossarm, 10ft	1				

Design Parameters:

- Maximum Line Angle: 2°

Notes:

**24.9/14.4 kV, 3-PHASE SINGLE
PRIMARY SUPPORT, CROSSARM
CONST. LARGE CONDUCTOR**

RUS
11/7/2017
REV. C



VC1.11LRG