



ITEM	NO.	PART#	MATERIAL	ITEM	NO.	PART#	MATERIAL
a	3		Insulator, pin type	g	1		Crossarm, 3 5/8" x 4 5/8" x 10'-0"
b	1		Pin, pole top, 20"	j	2		Screw, lag, 1/2" x 4" (VC1.12R only)
c1	2		Bolt, machine 1/2" x req'd length	bs	1		Bolt, single upset
c2	5		Bolt, machine 5/8" x req'd length	cm	1		Insulator, spool - 3"
d1	2		Washer, round 1/2"	cu	2		Brace, wood, 36"
d2	7		Washer, square 2" x 2" x 11/16"	ec	1		Bracket, offset neutral (VC1.12R only)
d3	1		Washer, curved 3" x 3" x 11/16"	ek	8		Locknuts
f	2		Pin, crossarm, steel, 5/8" x 14"	rp1	2		Perch Guard 36"
rp5	1		Perch Guard 30"	rp6	1		Perch Guard Pole Top
				rp7	2		Perch Guard Extenders

NOTES:

DESIGN PARAMETERS:  
2° Maximum

24.9 / 14.4 kV, 3-PHASE  
SINGLE PRIMARY SUPPORT, CROSSARM CONST.  
SMALL CONDUCTORS

RUS

11/10/08

Rev. A



VC1.11RG