



| ITEM | MATERIAL | QTY | ITEM | MATERIAL | QTY |
|------|-------------------------------------|-----|------|---------------------------------------|-----|
| a | Insulator, clamp top | 4 | aw | Washer, spring, 5/8" | 4 |
| c1 | Bolt, machine, 1/2" x req'd. length | 4 | az | Letters, 2 "C" & 2 "N", with 1" nails | 4 |
| c2 | Bolt, machine, 5/8" x req'd. length | 3 | cm | Insulator, spool - 3" | 2 |
| d1 | Washer, round - 1/2" | 4 | cu | Brace, crossarm, wood, 36" | 4 |
| d2 | Washer, square, 2" x 2" x 11/16" | 14 | da | Clevis, rigid | 2 |
| f | Pin, crossarm, steel | 6 | ek | Locknuts | 15 |
| g | Crossarm, 3 5/8" x 4 5/8" x 10'-0" | 2 | rp-1 | Salisbury coverup | 16' |
| n | Bolt, Double-arming, 5/8" | 4 | a | Insulator, pin type | 2 |

DESIGN PARAMETERS:
See TABLE IV

24.9 / 14.4 KV, 3-PHASE
DOUBLE SUPPORT, NEUTRAL ON CROSSARMS
SMALL CONDUCTORS

| | | |
|----------|--|---------|
| RUS |  | VC2.51R |
| 05/05/11 | | |
| Rev. A | | |