



ITEM	PART #	MATERIAL	QTY	ITEM	PART #	MATERIAL	QTY
a1	4310	Insulator, (24.9/14.4 KV)	8	n2	9364-	Bolt, DA, 3/4" X Req'd Length	2
a2	4311	Insulator, Clamp Type, (24.9/14.4 KV)	4	s	2155	Clevis, Rigid	1
c1	9371-6	Bolt, Machine, 1/2" X 6"	8	aw	9100	Double Coil Lock Washer, 1/2"	12
c2	9372-	Bolt, Machine, 5/8" X Req'd Length	2	bi	9233	Pole Gain	1
d1	9098	Washer, Round, 1/2"	8	cu	2035	Brace, Crossarm 60"X18"	4
d2	9091-3-5/8	Washer, Square 3" X 3" X11/16"	26	cu2	2040	Brace, Crossarm 84"X24"	4
d3	9092	Washer, Square 3" X 3" X11/16" Curved	1	da	9472	Insulator, Spool -4"	1
d4	9091-4	Washer, Square 4" X 4" X 13/16"	4	ek	9094	Locknut, 1/2"	8
f	4375	Pins, crossarm saddle	12	ek	9096	Locknut, 5/8"	18
g1	4120	Wood Crossarm, 3 5/8"X4 5/8"X8'-0"	2	ek	9097	Locknut, 3/4"	4
g2	4090	Wood Crossarm, 3 5/8"X4 5/8"X10'-0"	2	rp	4715	Salisbury Coverup	16'
n1	9363-	Bolt, DA, 5/8" X Req'd Length	8				

**DESIGN PARAMETERS:**

- Bulletin 1728F-803 Table V (up to 21° for 336.4 ACSR)

**NOTES:**

- SALISBURY COVER UP TO EXTEND 3' BEYOND EACH CROSSARM.

**DOUBLE SUPPORT ON CROSSARMS  
(TANGENT) ( LARGE CONDUCTORS)  
DOUBLE CIRCUIT PRIMARY  
24.9/14.4 kV**

RUS  
11/7/2017  
REV. C



**VD2.91LR**