



ITEM	NO.	PART#	MATERIAL	ITEM	NO.	PART#	MATERIAL
a	6	4310	Insulator, pin type	g	2	4090	Crossarm, 3 5/8" x 4 5/8" x 10'-0"
ek	4	9094	Locknuts - 1/2"	n	4	9363	bolt, double arming, 5/8" x req'd length
ek	12	9096	Locknuts - 5/8"	aw	4	9100	Washer, spring
c1	4	9371	Bolt, machine 1/2" x req'd length	bs	1	9376	Bolt, single upset
c2	3	9372	Bolt, machine 5/8" x req'd length	cm	1	4270	Insulator, spool - 3"
d1	4	9098	Washer, round 1/2"	cu	4	2040	Brace, wood, 44"
d2	13	9091	Washer, square 2" x 2" 11/16"	rp1	4	9356	Perch Guard 36"
b	2	4420	Pin, pole top, offset	rp5	2	9359	Perch Guard 30"
f	4	4375	Pin, crossarm, steel, clamp type	rp6	2	9358	Perch Guard Pole Top
rp5a	4	9352	Buckles 1/2" Zena raptor Guard	rp7	4	9354	Extender Guard
rp5b	8	9351	Banding 1/2" Zena raptor Guard				

DESIGN PARAMETERS:  
2° Maximum

24.9 / 14.4 KV, 3-PHASE  
DOUBLE PRIMARY SUPPORT, CROSSARM CONST.  
LARGE CONDUCTORS

RUS

09/17/09

Rev. A



VC2.20LRG