



| ITEM | NO. | PART# | MATERIAL | ITEM | NO. | PART# | MATERIAL |
|------|-----|-------|-----------------------------------|------|-----|-------|--|
| a | 6 | | Insulator, pin type | g | 2 | | Crossarm, 3 5/8" x 4 5/8" x 10'-0" |
| b | 2 | | Pin, pole top, offset | n | 4 | | bolt, double arming, 5/8" x req'd length |
| c1 | 4 | | Bolt, machine 1/2" x req'd length | aw | 4 | | Washer, spring |
| c2 | 4 | | Bolt, machine 5/8" x req'd length | cm | 1 | | Insulator, spool - 3" |
| d1 | 4 | | Washer, round 1/2" | cu | 4 | | Brace, wood, 44" |
| d2 | 12 | | Washer, square 2" x 2" x 11/16" | da | 1 | | Clevis, rigid |
| d3 | 1 | | Washer, curved 3" x 3" x 11/16" | ek | 16 | | Locknuts |
| f | 4 | | Pin, crossarm, steel, clamp type | rp1 | 4 | | Perch Guard 36" |
| rp5 | 2 | | Perch Guard 30" | rp6 | 2 | | Perch Guard Pole Top |
| | | | | rp7 | 4 | | Perch Guard Extenders |

DESIGN PARAMETERS:
See Table III

24.9 / 14.4 KV, 3-PHASE
DOUBLE PRIMARY SUPPORT, CROSSARM CONST.
LARGE CONDUCTORS

RUS
03/02/2009
Rev. A



VC2.21LRG