


ITEM	NO.	PART#	MATERIAL	ITEM	NO.	PART#	MATERIAL
a	6		Insulator, clamp top	aw	8		Washer, spring, 5/8"
c1	4		Bolt, machine, 1/2" x req'd. length	az	4		Letters, 2 "C" & 2 "N", with 1" nails
c2	3		Bolt, machine, 5/8" x req'd. length	cm	2		Insulator, spool - 3"
d1	4		Washer, round - 1/2"	cu	4		Brace, crossarm, wood, 44"
d2	22		Washer, square, 2" x 2" x 11/16"	da	2		Clevis, rigid
f	6		Pin, crossarm, steel, clamp type	ek	19		Locknuts
g	2		Crossarm, 3 5/8" x 4 5/8" x 10'-0"	rp	3		Salisbury coverup
n	6		Bolt, Double-arming, 5/8"	rp2	4		perch Guard 24"
rp5	2		Perch Guard 30"	rp7	8		Perch Guard Extender
				rp8	1		Perch Guard Pole Top Cone

Notes:

DESIGN PARAMETERS:
See TABLE V

**24.9 / 14.4 KV, 3-PHASE
DOUBLE SUPPORT, NEUTRAL ON CROSSARMS
LARGE CONDUCTORS**

RUS		VC2.51LRG
11/12/08		
Rev. A		