



ITEM	NO.	PART#	MATERIAL	ITEM	NO.	PART#	MATERIAL
c2	1	9372	Bolt, machine 5/8" x req'd length	n	1	9364	Bolt, double arming 3/4" x req'd length
c4	1	9373	Bolt, machine 3/4" x req'd length	o	1	9368	Bolt, oval eye, 5/8" x req'd length
d2	2	9091	Washer, Square 2" x 2" x 11/16"	s	2	9340	Clevis, swinging
d3	2	9092	Washer, curved 3" x 3" x 11/16"	aa4	1	4342	Nut, eye 3/4"
d4	2	9093	Washer, curved 3" x 3" x 13/16"	cm	1	4271	Insulator, spool 4"
g	1	4118	Crossarm, fiberglass, 10'	ek	4	9096/7	Locknuts
k	3	4280	Insulators, polymer distribution deadend, 18.75"	eu	1	4281	Link, extension fiberglass
1	3	9061	Clamp, deadend- Preform	rp5	4	9359	Perch Guard 30" Zena
	3	2125	Deadend Shoe 336.4	rp8	1	9350	Guard Pole Top Cap

DESIGN PARAMETERS:

Allowable Longitudinal Load Equals
 Lesser of:
 5,000 lbs/Conductor or Manufacturer's
 Specifications

**24.9 / 14.4 KV, 3-PHASE
 SINGLE DEADEND ON CROSSARM ASSEMBLY
 LARGE CONDUCTORS**

RUS

11/05/09

Rev. A



VC5.71LRG