



ITEM	PART #	MATERIAL	QTY	ITEM	PART #	MATERIAL	QTY
a	4311	Insulator, Clamp Type 25kV	1	s	2160	Clevis, Swinging	2
c	9372	Machine Bolt, 5/8"	1	av	3114	Jumper, Insulated	8'
c2	9373	Machine Bolt, 3/4"	2	cm	9471	Insulator Spool	2
d	9091	Washer, Square 2" X 2"	2	ek	9096	Locknuts, 5/8"	1
d2	9093	Washer, Curved	2	ek	9097	Locknuts, 3/4"	2
f	4370	Pin, Crossarm	1	rp1	4766	Perch Guard 36"	1
g	4118	Crossarm, Fiberglass 10'	1	rp5	4780	Zena Perch Guard	3
k	4280	Insulator Epoxilator, 18.75"	2	rp6	4743	Pole Cap	1
l	2120	Deadend Clamp	2	rp7	4769	Perch Guard Extension	1

NOTES

1. Maximum line angle: 5° (see note 2).
2. Maximum line angle may be increased to 15° by installing anchor shackles, item "bo" to (horizontal) eyenuts and installing side guys as required.
3. Allowable unbalanced longitude tension: 1,000 lbs./conductor.

**DOUBLE DEADEND 10' CROSS ARM
1 PHASE HIGH NEUTRAL 14.4 kV**

RUS
9/15/20
Rev. B



VA6.22RG