



ITEM	PART #	MATERIAL	QTY	ITEM	PART #	MATERIAL	QTY
c2	9372	Bolt, Machine 5/8" X Req'd Length	1	o	9368	Bolt, Oval Eye 5/8" X Req'd Length	1
c4	9373	Bolt, Machine 3/4" X Req'd Length	1	s	2160	Clevis, Swinging	1
d2	9091	Washer, Square 2" X 2 X 11/16"	2	aa	9878	Eyenut 3/4"	1
d3	9092	Washer, Curved 3" X 3" X 11/16"	2	cm	9471	Insulator, Spool 3"	1
d4	9093	Washer, Curved 3" X 3" X 13/16"	2	eu	4281	Link, Fiberglass Extension	1
g	4118	Crossarm, Fiberglass 10' Deadend	1	ek	9096	Locknut 5/8"	1
k	4280	Insulator, Expoxilator 18.75"	3	ek	9097	Locknut 3/4"	3
l	2120	Clamp, Deadend	3	rp5	4780	Perch Guard 30" Zena	4
n	9364	Bolt, Double Arming 3/4" X Req'd Length	1	rp8	4743	Perch Guard Pole Top Cone	1

DESIGN PARAMETERS:

Allowable Longitudinal Load: Lesser of 5,000 lbs./conductor or manufacturer's specification

**24.9/14.4kV, 3-Phase
Single Deadend on Crossarm Assembly
Small Conductor**

RUS
9/16/2020
REV. B



VC5.31DRG